

Stager Controller

www.kangjiezc.com | jk@kangjiezc.com | +86-10-69730336



48-*/51-*/58-* SERIES COMMERCIAL STAGER CONTROLLERS



Full-Function Programming with capability to link multiple stagers

FEATURES

- Front panel diagnostics information :
 - Date & Time
 - Interlocked Mode
 - Service Mode
 - Flow rate
 - Regeneration Status
 - Service parameters under different mode
- Can be used with time clock or meter immediate
- Allows regeneration by remote signal
- Controller and stager automatically synchronize to the service position
- Accepts input from a variety of flow sensors
- During a power outage, critical operating information is stored in memory
- Programmable regeneration types for increased flexibility
- Easy installation

TECHNICAL SPECIFICATION

Controller Model	JKA2.1 (CE certified, Interlocked Function)
Power	85-250/AC, 50/60Hz, 4W
IP Rating	IP54
Working Temperature	4-60°C
Dimension	300×230×160
Language	English
Application	Filtration/Softener

JKA2.1 APPLICATIONS

Single Unit Controller	Model No.	Description
Typical Softeners and Filters	JKA2.1-48-*	48-* Controller, 6 Port Stager
More Complex Softeners and Filters	JKA2.1-51-*	51-* Controller, 8 Port Stager
2 tank softeners	JKA2.1-58-*	58-* Controller, 16 Port Stager



SOFTENTING SYSTEM OPERATING MODES

System Description	JKA2.1	Type
Single Unit	1	Time Clock: No Meter Immediate: One Meter Remote: No Meter
Interlocked D mode	2-9	Multiple Tank Alternating Time Clock: No Meter Immediate: All Meters
Interlocked E mode	2-9	Series Regeneration Time Clock: No Meter Immediate: All Meters