

2026 Can-Am Outlander MAX XT 850 Price in Kaliningrad is 1 630 000P



Condition	New
Model Year	2026
Manufacturer	Can-Am
Model	Outlander MAX XT 850
VIN	3JB3PA642TJ000693
Color	Platinum Satin
Brakes/Wheels/Tires	
Brakes	Front - Dual 214 mm disc with hydraulic twin-piston calipers Rear - Single 214 mm disc with hydraulic twin-piston caliper Standard
Wheels	14 in. Aluminum
Tires	Front / Rear - XPS Trail King 2 - 26 x 8/10 x 14 in.
Dimensions	
Length	99 in. (252 cm)
Height	56.4 in. (143.2 cm)
Width	48.5 in. (123.2 cm)
Weight	Estimated dry - 998 lb. (453 kg)
Ground Clearance	11.5 in. (29.2 cm)
Wheelbase	60.8 in. (154.4 cm)
Seat Height	37.8 in. (96 cm)
Drivetrain	
Transmission	pDrive primary CVT L / H / N / R / P
Drive System	4x4
Drive	Drive train - Selectable 2WD / 4WD with Visco-Lok† QE auto-locking front differential Driving assistance - Work / Standard / Sport modes Intelligent Engine Braking (iEB™)
Electrical	
Alternator	Magneto - 650W
Instrumentation	Phone storage & USB-C charger Gauge - 7.6 in. wide digital display
Lighting	LED headlights and taillights
Engine	
Engine	850 Type - Rotax V-twin, DOHC
Cooling	Liquid cooled Radiator cooling fan of 80W & 150 cm ³
Horsepower	82 hp
Displacement	999 cc
Torque	66 ft. lb.
Fuel System	Fuel delivery system - Intelligent Throttle Control (iTCT™) with Electronic Fuel Injection (EFI)
Ignition	RF Digitally Encoded Security System (D.E.S.S.™)
Fuel Capacity	5.1 gal. (19.5 l)
Operational	
Suspension	Front - Arched Double A-arm 10.8 in. (27.4 cm) travel Rear - Arched Double A-arm 12 in. (30.5 cm) travel
Standard	Front / Rear shocks - Twin tube

Steering	Tri-Mode Dynamic Power Steering (DPS)
Seating	Removable passenger
Hitch	Type - 2 in. receiver
Towing Capacity	1,830 lb. (830 kg)
	Winch - Can-Am HD 3,500 lb. (1,588 kg) with synthetic cable
Load Capacity	Front rack capacity - 120 lb. (54.4 kg)
	Rear rack capacity - 240 lb. (109 kg)
Capacity	Storage - 10.6 gal. (40 l)
Other	
Includes	Protection - Full skid plate, Heavy Duty front and rear bumpers, Handguards Handlebar - Standard