

2025 Indian Motorcycle Chieftain PowerPlus Dark Horse with PowerBand Audio **Price in Kaliningrad is 2 750 000P**



Condition	New
Model Year	2025
Manufacturer	Indian Motorcycle
Model	Chieftain PowerPlus Dark Horse with PowerBand Audio
Category	PowerPlus
VIN	56KLFDRR3S3434946
Color	Black Smoke

Brakes/Wheels/Tires

Brakes	Front - Brembo® Calipers, Dual Semi-Floating Rotors, 320 x 5.0 mm Rear - Single Floating Rotor, 298 x 7.0 mm ABS
Wheels	Front - 10-Spoke Machined Cast 19 x 3.5 in. Rear - 10-Spoke Machined Cast 16 x 5 in.
Tires	Front - Metzeler® Cruisetec® 130 / 60B19 66H Rear - Metzeler® Cruisetec® 180 / 60R16 80H

Dimensions

Length	Overall - 98.5 in. (2,503 mm)
Height	Overall - 48.7 in. (1,237 mm)
Width	Overall - 41.9 in. (1,063 mm)
Weight	As Shipped - 806 lb. (366 kg) Running Order - 842 lb. (382 kg) GVWR - 1,385 lb. (628 kg)
Ground Clearance	5.4 in. (137 mm) Lean Angle - 31°
Wheelbase	65.7 in. (1,668 mm)
Seat Height	26.5 in. (686 mm)

Drivetrain

Primary Drive	Gear Drive Wet Clutch
Final Drive	2.379 : 1

Electrical

Instrumentation	Gauges - Fairing-mounted instrument cluster featuring analog speedometer and tachometer with fuel gauge, range, odometer and current gear. 15 LED telltale indicators, cruise control enabled, cruise control set, neutral, high beam, turn signal, ABS, check engine, low tire pressure, battery, low fuel, security system, low engine oil pressure and MPH or km/h unit designation Infotainment - A 7 in. Display Powered by RIDE COMMAND with Turn-by-Turn GPS Navigation, Customizable Gauge Screens, Bluetooth® Connectivity, AM / FM Radio, Selectable Ride Modes, and More. Factory-Installed RIDE COMMAND+ Telecommunications Unit (TCU) for One-Year FREE Provides Live Weather and Traffic Overlays, Apple CarPlay®, Bike Health, Bike Locator, Intuitive Destination Search, and More Audio - Upgraded PowerBand 2.0 Audio package Audio - Includes - 2 - 100W fairing speakers, 2 - 100W saddlebag speakers, 400W total
Lighting	LED Headlamp / Tail / Brake / Turn Signal

Engine

Engine	PowerPlus
Cooling	Liquid
Horsepower	122 hp
Displacement	1,768 cc (108 ci)
Bore x Stroke	4.25 x 3.8 in. (108 x 96.5 mm)
Compression Ratio	11.0 : 1
Gear Ratio	1st - 10.169 : 1 2nd - 6.933 : 1 3rd - 5.151 : 1 4th - 4.105 : 1 5th - 3.508 : 1 6th - 3.017 : 1
Clutch	Wet, Multi-Plate, Assist
Fuel System	Closed loop fuel Injection / 52 mm dual bore
Exhaust	Split with Resonator
Ignition	Keyless
Fuel Capacity	6.0 gal. (22.7 l)
Peak Torque	128 ft. lb. @ 3,800 rpm
Operational	
Front Suspension	Inverted Telescopic Fork Travel - 5.1 in. (130 mm)
Rear Suspension	Single Shock with Hydraulic Preload Adjustment Travel - 4.5 in. (114 mm)
Rake	25°
Trail	5.9 in. (150 mm)
Fork	Front Tube Diameter - 43 mm