

2025 Kawasaki Ninja ZX-6R ABS Price in Kaliningrad is 1 350 000P



Condition	New
Model Year	2025
Manufacturer	Kawasaki
Model	Ninja ZX-6R ABS
Category	Supersport
VIN	JKBZXJJ14SA028886
Color	Metallic Matte Dark Gray / Ebony

Brakes/Wheels/Tires

Brakes

Front - Dual semi-floating 310 mm discs with dual radial-mounted, monobloc, opposed 4-piston caliper, Kawasaki Intelligent anti-lock Brake System (KIBS)

Rear - Single 220 mm petal discs with single-piston caliper, Kawasaki Intelligent anti-lock Brake System (KIBS)

ABS (Anti-Lock Brake System)

Tires

Front - 120 / 70 ZR17

Rear - 180 / 55 ZR17

Pirelli Diablo™ Rosso IV

Dimensions

Length

Overall - 79.7 in.

Height

Overall - 43.3 in.

Width

Overall - 28.0 in.

Weight

Curb - 434.4 lb.* (*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.)

Ground Clearance

5.1 in.

Wheelbase

55.1 in.

Seat Height

32.7 in.

Drivetrain

Transmission

6-speed, return shift

Final Drive

Sealed chain

Electrical

Instrumentation

4.3 in. Full-Color TFT, Smartphone Connectivity via RIDELOGY THE APP

Economical Riding Indicator

Lighting

All-LED

Advanced Electronics

Electronic Rider Aids - Kawasaki Traction Control (KTRC), Power Modes (Full/Low)

Engine

Engine

4-stroke, DOHC, 16-valve

Cooling

Liquid

Cylinders

In-line 4

Displacement

636 cc

Power

122hp

Bore x Stroke

2.3 x 1.8 in. (67 x 45.1 mm)

Torque

Maximum - 52.1 lb. ft. @ 10,800 rpm

Compression Ratio

12.9:1

Clutch

Assist and slipper

Fuel System

DFI® with 38 mm Keihin throttle bodies (4) and oval sub-throttles

Ignition

TCBI with digital advance

Fuel Capacity	4.5 gal.
Operational	
Frame	Type - Aluminum perimeter
Front Suspension	41 mm inverted fork Showa Separate Function Big Piston Fork (SFF-BP) with rebound and compression damping and spring preload adjustability, and top-out springs Wheel Travel - 4.7 in.
Rear Suspension	Bottom-link Uni-Trak® with single shock, stepless compression damping adjustment, stepless adjustable rebound damping, fully adjustable spring preload Wheel Travel - 5.9 in.
Rake	23.5°
Trail	4.0 in.
Throttle	Dual Throttle Valves
Shifter	Kawasaki Quick Shifter (KQS) (upshift only)