


2025 Can-Am Maverick X3 Max X RS Turbo RR With Smart-Shox
Price in Kaliningrad is 6 430 000P





- Condition New
- Year 2025
- Make Can-Am
- Model Maverick X3 Max X RS Turbo RR With Smart-Shox
- Vehicle Type Utility Vehicle
- VIN 3JBVNAV44SE000007
- Color Nriple Black

Manufacturer Info

- Engine TURBO RR | Rotax ACE (Advanced Combustion Efficiency) 900 cc Turbocharged Triple-cylinder engine
- Engine Type 200 hp
- Engine Power liquid cooled with integrated intercooler and high-performance air filter
- Cooling System 900 cc
- Displacement Intelligent Throttle Control (iTCT™) with Electronic Fuel Injection (EFI)
- Fuel System
- Drivetrain Lockable front differential with exclusive Smart-Lok True
- Drivetrain 2WD/4WD with front diff. lock / 4WD TRAIL ACTIV / 4WD TRAIL
- Transmissionp Drive primary and Quick Response System X (QRS-X) CVT with high airflow, L / H / N / R / P
- Steering Power: High torque Tri-Mode Dynamic Power Steering (DPS™)

- Suspension
- Front Suspension Double A-arm with sway bar
- Front Travel (in./cm.) 22 in. (55.9 cm) suspension travel Trophy truck inspired arms
- Front Shocks FOX† 2.5 PODIUM† Piggyback with bypass and Smart-Shox Technology featuring DDA Valve (Dynamic Damping Adjustment)
- Rear Suspension 4-link Torsional Trailing-arm X (TTX) with sway bar
- Rear Travel (in./cm.) 22 in. (55.9 cm)
- Rear Shocks FOX† 3.0 PODIUM† Piggyback with bypass and Smart-Shox Technology featuring DDA Valve (Dynamic Damping Adjustment) Smart-Shox was developed in conjunction with Tractive Industries, a market leader in the suspension industry
- Brakes
- Front braking system Dual 262 mm disc brakes with hydraulic twin-piston calipers
- Rear braking system Dual 248 mm disc brakes with hydraulic twin-piston calipers
- Wheels & Tires
- Wheels 15 in. cast-aluminum beadlock
- Front Tire XPS Trac Force 32 x 10 x 15 in.
- Rear Tire XPS Trac Force 32 x 10 x 15 in.
- Dimensions
- Overall Vehicle Size (LxWxH) 165 x 72.7 x 68.5 in. (419.1 x 184.7 x 174 cm)
- Wheelbase 135 in. (342.9 cm)
- Ground Clearance 16 in. (40.6 cm)
- Capacities
- Storage Capacity Total: 3 gal (11.4 L)
- Rack capacity, total 150 lb (68 kg) with LinQ™ quick-attach
- Fuel Capacity 10.5 gal (40 L)
- Weights
- Estimated Dry Weight (lbs./kgs.) 1,942 lb (880.9 kg)
- Features
- Instrumentation DC outlet (10-A)
- Features Anti-Theft System: RF Digitally Encoded Security System (D.E.S.S.™) with Start/Stop button
- Cage Type Dual-phase 980 steel
- Protection Plan Integrated front bumper, Quarter-doors, Full hard roof, 4-point harness with shoulder pads, HMWPE full skid plate, Rear tow hook
- Magneto 850-W
- Gauges 7.6 in. digital display with keypad
- Lights and Safety
- Lighting LED headlight, LED signature, LED tail lights