

**2025 BMW K 1600 GTL Price in Kaliningrad is 4 900 000P**



Condition	New
Model Year	2025
Manufacturer	BMW
Model	K 1600 GTL
Category	Touring
VIN	WB10F3303S6K72681
Color	Black Storm Metallic

## **Brakes/Wheels/Tires**

Brakes	Front - Dual disc, diameter 320 mm, 4-piston fixed calipers Rear - Single disc, diameter 320 mm, double-piston caliper ABS - BMW Motorrad Integral ABS Pro (part-integral, slant-layer-optimized)
Wheels	Cast aluminum
Rims	Front - 3.5 x 17 in. Rear - 6 x 17 in.
Tires	Front - 120 / 70 ZR 17 Rear - 190 / 55 ZR 17

## **Dimensions**

Length	Over top case - 98 in.
Height	At windshield and top case - 58.7 - 62.2 in.
Width	Including side cases - 39.4 in.
Weight	Unladen, road ready, fully fuelled - 789 lb. Permitted total - 1,234.6 lb.
Wheelbase	63.7 in.
Seat Height	29.5 in. Inner leg curve - 69.3 in.

## **Drivetrain**

Transmission	Gearbox - 6-speed, helical
Drive System	Shaft

## **Electrical**

Battery	12V / 16Ah
Alternator	Three-phase with 700W (nominal power)
Instrumentation	10.25 in. Color-TFT display with connectivity and integrated map-navigation (by BMW Motorrad Connected App)
Lighting	Fully LED headlight with light icon and adaptive cornering
Advanced Electronics	4 configurable favorite button cluster Dynamic traction control (DTC) 3 Ride Modes Rain, Road and Dynamic Engine brake control (MSR) Dynamic ESA (electronic suspension adjustment with automatic load leveling) Hill Start Control (HSC Pro) Tire Pressure Monitor (TPM) Reverse Assist Audio system 2.0 with SAT-radio and sound-profiles

## **Engine**

Engine	Four-stroke, in-line engine with four valves per cylinder
Cooling	Oil / Water
Cylinders	6
Horsepower	160 hp @ 6,750 rpm
Displacement	1,649 cc

Bore x Stroke	2.83 x 2.66 in. (72 x 67.5 mm)
Torque	Max. - 132.7 lb. @ 5,250 rpm
Compression Ratio	12.2 : 1
Clutch	Multiple-disc in oil bath
Fuel System	Mixture control - Electronic intake pipe injection digital engine management system - BMS-O with throttle-by-wire
Emissions	Control - Closed-loop 3-way catalytic converter
Ignition	Keyless Ride
Fuel Type	Unleaded super (max. 15 % Ethanol, E15) / ROZ 95 / 90 AKI
Fuel Capacity	Usable tank volume - Approx. 7 gal.
Reserve - Approx. 1 gal.	Operational
Frame	Bridge-type, cast aluminum, load-bearing engine
Front Suspension	BMW Motorrad Duolever, central spring strut Travel - 4.5 in.
Rear Suspension	Cast aluminum single-sided swing arm with BMW Motorrad Paralever; central spring strut Travel - 5.3 in.
Rake	Steering head angle - 62.2°
Trail	Castor - 4.2 in.
Maximum Speed	120+ mph
Capacity	Payload (with standard equipment) - 445 lb.
Seat	Heating
Grips	Heated
<b>Other</b>	
Includes	Charging storage for mobile phones (USB-C) Double tone fanfare Side cases Top case ECall Intelligent Emergency Call Complimentary BMW Motorrad Ultimate Care Break-In Service